

EPSON Projector [EB-1770W] Specifications

Projection System		Epson 3LCD
Brightness		3000 lm
Contrast ratio		2000:1
LCD panel size(diagonal)		0.59
LCD panel pixels(W x H x pcs)		1280x800x3LCD
Color Reproduction		16.77million full color
Main unit size(WxDxH)		292x210x44(mm): Excluding feet
Weight		Approx. 1.7kg
RGB signal resolution		Analog: UXGA, SXGA+, SXGA, WXGA+, WXGA (real), XGA, SVGA, VGA Digital:UXGA, SXGA+, SXGA, WXGA+, WXGA (real),XGA, SVGA, VGA
Video signal		NTSC/PAL/SECAM D4, DVD component
Scanning Frequency	Analog RGB	Horizontal 15-92kHz, Vertical 50-117Hz
Projection Lens	F-number	1.58-1.7
	Focal Length:f(mm)	13.52-16.22
	Zoom Ratio	1.2
	Zoom/Focus	Manually
Illuminant out/type		205W UHE
Operating Temperature		5-35°C
Power Supply		AC100-120V/200-240V ±10% 50/60Hz
Power Consumption		Normal:322W, Eco:212W Communication on:7.7W, standby:0.4W
Video Interface	IN	Mini D-Sub15pin, RCA, HDMI
Interface	OUT	-
Audio Interface	IN	Stereo mini
Interface	OUT	-
Control Interface		USB B-type(For USB Display, For projector control)
Speaker		1W
Interface		Computer / Component video: Mini D-sub HD 15 pin x 1, Composite video: RCA x 1, Audio in: Mini stereo x 1 USB connector: Type B x 1 (USB display with audio and mouse / keyboard control), Type A x 1 (for USB memory device), HDMI x 1
Other function		Keystone Correction (Manual: Vertical: ±45 degrees, Manual: Horizontal: ±30 degrees) (Automatic: Vertical: ±30 degrees) Direct power on, Single touch off, slideshow Effect function(pointer), User logo projection Password protect, color mode(9type), Blackboard mode Digital magnification, Freeze/AV mute Remote mouse, help information display
Supplied accessory		AC cable(100V: domestic Japan only) Mini D-Sub15pin RGB cable(1.8m),RCA cable, USB cable(3m) HDMI cable(1.8m), audio adaptor, remote control, battery for remote control Soft carrying case, Handling manual(CD-ROM), Setup guide