



EPSON Projector [EB-1940W] Specifications

Projection System		High-aperture Epson 3LCD, 3-chip technology
Brightness		4200lm
Contrast ratio		3000 :1
LCD panel size(diagonal)		0.59
LCD panel pixels(W x H x pcs)		1280x800x3LCD
Color Reproduction		16.77million full color
Main unit size(W x D x H)		377x271x93(mm)
Weight		Approx. 3.7kg
RGB signal resolution		Analog:UXGA, SXGA+, SXGA, WXGA+, WXGA(real), XGA, SVGA, VGA Digital: UXGA, SXGA+, SXGA, WXGA+, WXGA(real), XGA, SVGA, VGA
Video signal		NTSC/PAL/SECAM D4/DVD component
Scanning Frequency	Analog RGB	Horizontal 15-92kHz, Vertical 50-85Hz
	Digital RGB	Horizontal 15-75kHz, Vertical 24Hz/30Hz/50Hz/60Hz
Projection Lens	F-number	1.51-1.99
	Focal Length:f(mm)	18.2-29.2
	Zoom Ratio	1.0-1.6
	Zoom	Manual
	Focus	Manual
Lamp type		245W UHE
Operating Temperature		5-35°C
Power Supply		AC100-120V/200-240V ±10% 50/60Hz
Power Consumption		Normal: 353W, Eco:258W, Communication on: 3.8W, Standby:0.4W
Video interface	IN	Mini D-Sub15pin(x2), RCA, DisplayPort, HDMI
	OUT	Mini D-Sub15pin
Audio interface	IN	RCA[R/L], Stereo mini(x2)
	OUT	Stereo mini
Control Interface		RS-232C (For Projector control) USB type-B (For Remote mouse and projector control) RJ45(For network)
PC card slot		-
USB storage		USB type-A
Speaker		10W
Interface		DisplayPort, HDMI, Computer: D-sub 15 pin x 2 Video: RCA Wired Network: RJ-45 Serial: RS-232c Monitor-Out: D-sub 15 pin USB (Type A): For PC-free and document camera USB (Type B): For computer
Other function		Wired LAN, USB Display, Slideshow, E-Mail notification Keystone Correction (Manual Vertical: ±30 degrees, Auto Vertical: ±30 degrees, Auto Horizontal:±30 degrees). Direct power on, direct shut down Effect function(pointer), user logo projection, password protect, color mode (8type), blackboard mode Digital magnification(Max: x4 (area ratio: x16)) Freeze/AV mute, remote mouse Wired remote control (option), help information display
Supplied accessory		AC cable(100V: domestic Japan only) Mini D-Sub15pin RGB cable, remote control/ battery for remote control USB mouse cable, lens cover, instruction manual, quick reference software CD-ROM(EMP Monitor, EMP NS Connection, EMP Slide Maker2)